

Model Name

Automatic Transfer Switch (ATS)

Model Number

ATP-1511A-10-N1

15Amp 115V



General

Output	(10) NEMA 5 -15/20R
Input	(2) IEC320 C20 Inlet; Enclosed C19 to NEMA5 -15P plugs 3 Meters

Communication

DHCP Indication	(1) Green LED
Output Status	(2) Green LED
Input Status	(2) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
Identification	1 Digits Seven Segments for Identification
Meter	3 Digits Seven Segments

Power Information

Voltage	+/- 2% @ 90V-260V
Active Power	+/- 2% @ 50W-5000W
Apparent Power	+/- 2% @ 50VA-5000VA
Frequency	+/- 2% @ 45-65Hz
Power Factor	+/- 0.02 @ 0.5-1.0
kWh	Range: 0.001kWh ~ 99999.999kWh Precision: +/- 2% @ 50W-5000W, kh=1.0
Current	Range: 0A ~ 32 A Resolution: 0.1A Precision: +/- 2% +/- 0.1AMP

Operation

Nominal Voltage	110V ~130V
On-Line Voltage	100V- 143V
Frequency	50/60Hz
Max. Output	15 Amp
Transfer Time	8-16ms
Operation Temp.	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	260 x 432 x 44.45 mm
Net Weight	5 kg

Regulatory Approvals



Meter True RMS Current Meter,

Power Monitor Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

Protocols TCP/IP, SNMP, DHCP, UDP

Installed in Rack Horizontal

Power Action Automatic Transfer Switch

Event Alert Email, Trap

Option Device Temp./Humidity Probe



Package

No	Description
1	PDU 1 set
2	Rack mount accessories 1 set
3	Software CD (manual, MIB)
4	(2) C19 to NEMA5-15P, power cord, 3 m

Accessory

Model Number	Model Name
CPM-ENV-2	Temp./Humidity probe

Line Drawing

