

Model Name
Metered PDU



Model Number
ATP-M-2011B-08-N1

20Amp 115V





Meter True RMS Current Meter,

Power Monitor Total Power Monitoring by Meter. Work with [Cabinet Power Monitor](#)

Alarm Thresholds Warning and Overload

Event Alert Audible Alarm

General	
Output	(8) NEMA5 -15/20R
Input	(1) NEMA 5 -20P attached power cord, 3 meters long
Protection	(1) 20 AMP Circuit Breaker
Communication	
Link Status	(1) Yellow LED
Power Status	(1) Green LED
Power Monitor (Option)	(1) RJ11, ready for connecting to Cabinet Monitor
Operation	
Nominal Voltage	115V
Voltage	100V~127V
Frequency	50/60HZ full range
Max. Output Current	20 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	44 x 431.5 x 44 mm
Weight	1.8 kg
Regulatory Approvals	 



Model Name
Metered PDU



Model Number
ATP-M-2020Q-08-N1

20Amp 208V



Meter True RMS Current Meter,

Power Monitor Total Power Monitoring by Meter. Work with [Cabinet Power Monitor](#)

Alarm Thresholds Warning and Overload

Event Alert Audible Alarm

General

Output	(8) IEC320 C13
Input	(1) NEMA L6 -20P attached power cord, 3 meters long
Protection	(1) 20 AMP Circuit Breaker

Communication

Link Status	(1) Yellow LED
Power Status	(1) Green LED
Power Monitor (Option)	(1) RJ11, ready for connecting to Cabinet Monitor

Operation

Nominal Voltage	208V
Voltage	208V
Frequency	50/60HZ full range
Max. Output Current	20 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	44 x 431.5 x 44 mm
Weight	1.6 kg

Regulatory Approvals



Model Name
Metered PDU



Model Number
ATP-M-1623K-08-N1

16Amp 230V



Meter True RMS Current Meter,

Power Monitor Total Power Monitoring by Meter. Work with [Cabinet Power Monitor](#)

Alarm Thresholds Warning and Overload

Event Alert Audible Alarm

General	
Output	(8) IEC320 C13
Input	(1) IEC320 C19 attached power cord, 3 meters long
Protection	(1) 16 AMP Circuit Breaker
Communication	
Link Status	(1) Yellow LED
Power Status	(1) Green LED
Power Monitor (Option)	(1) RJ11, ready for connecting to Cabinet Monitor
Operation	
Nominal Voltage	230V
Voltage	200V~240V
Frequency	50/60HZ full range
Max. Output Current	16 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	44 x 431.5 x 44 mm
Weight	1.6 kg
Regulatory Approvals	