

ATP-1511A-08-N8

15Amp 115V



General

Output	(8) NEMA 5 -15/20R
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to NEMA 5 -15P Power Cord 3 Meters long
Protection	(1) 15 AMP Circuit Breaker

Communication

DHCP Indication	(1) Green LED
Output Status	(8) Green LED
Circuit Status	(8) Red LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits for PDU Identification
Meter	3 Digits Seven Segments

Power Information

Voltage	+/- 2% @ 90V~260V
Active Power	+/- 2% @ 50W~5000W
Apparent Power	+/- 2% @ 50VA~5000VA
Frequency	+/- 2% @ 45~65Hz
Power Factor	+/- 0.02 @ 0.5~1.0
kWh	Range: 0.001kWh ~ 99999.999kWh Precision: +/- 2% @ 50W~5000W, kh=1.0
Current	Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- 2% +/- 0.1AMP

Operation

Nominal Input Voltage	115V
Output Voltage	100V~ 127V full range
Frequency	50/60HZ full range
Max. Output	15 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	215 x 432 x 44.45 mm
Net Weight	4 kg

Regulatory
Approvals



Meter True RMS Current Meter, Voltage, Frequency, Power Factor, Active Power, Apparent Power, Total kWh, Sub-total kWh.

Power Monitor Per Outlet Output Current and Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

Protocols TCP/IP, SNMP, DHCP, UDP

Outlet Control Individual, Group, Schedule, Auto Ping

Power Delay Power On/Off Sequence can be Defined

Alarm Thresholds User-Defined Alarm Thresholds for Warning and Overload

Event Alert Email, Trap, Audible Alarm

Temp./Humidity Option Accessory



Model Name
POM PDU



Model Number
ATP-1623K-08-N8

16Amp 230V



General

Output	(8) IEC320 C13
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 PowerCord 3 Meters long
Protection	(1) 16 AMP Circuit Breaker

Communication

DHCP Indication	(1) Green LED
Output Status	(8) Green LED
Circuit Status	(8) Red LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segments for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: + / -2%+ / -0.1AMP

Operation

Nominal Input Voltage	230V
Output Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	160 x 432 x 44.45 mm
Net Weight	3.5 kg

Regulatory Approvals
CE, CISPER 22, CISPER 24, IEC 61000-3-2,
IEC 61000-3-3
FCC Part 15 Class A, ICES-003



Meter True RMS Current Meter,

Power Monitor Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

Protocols TCP/IP, SNMP, DHCP, UDP

Outlet Control Individual, Group, Schedule, Auto Ping

Power Delay Power On/Off Sequence can be Defined

Alarm Thresholds User-Defined Alarm Thresholds for Warning and Overload

Event Alert Email, Trap, Audible Alarm

Temp./Humidity Option Accessory

