

Model Name  
**Switched PDU**



Model Number  
**ATP-2011B-24-N1**

20Amp 115V



**General**

Output	(24) NEMA 5 -15/20R
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to NEMA 5 -20P Power Cord 3 Meters long
Protection	(1) 20 AMP Circuit Breaker

**Communication**

DHCP Indication	(1) Green LED
Output Status	(24) Green LED
Network	(1) RJ45 for Ethernet
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/ -2%/ -0.1AMP

**Operation**

Nominal Voltage	115V
Voltage	100V~127V full range
Frequency	50/60HZ full range
Max. Output Current	20 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1778 x 44 mm
Weight	5.8 kg

**Regulatory Approvals**  
 CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3  
 FCC Part 15 Class A, ICES-003



**Meter** True RMS Current Meter,

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual,

**Power Delay** Power On/Off Sequence can be Defined

**Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload

**Event Alert** Email, Trap, Audible Alarm



Model Name  
**Switched PDU**



Model Number  
**ATP-3011M-16-N2**

30Amp 115V



General	
Output	(16) NEMA 5 -20/15R
Input	(1) NEMA L5 -30P attached power cord, 3 meters long
Protection	(2) 20 AMP Circuit Breaker
Communication	
DHCP Indication	(1) Green LED
Circuit Status	(2) Red LED
Output Status	(16) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segment for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- 2% +/- 0.1AMP
Operation	
Nominal Voltage	115V
Voltage	100V-127V full range
Frequency	50/60HZ full range
Max. Output Current	30 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1245 x 44 mm
Weight	4.5 kg
Regulatory Approvals	CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 FCC Part 15 Class A, ICES-003

**Meter** True RMS Current Meter

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual, Group, Schedule, Auto Ping

**Power Delay** Power On/Off Sequence can be Defined

**Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload

**Event Alert** Email, Trap, Audible Alarm

**Temp./Humidity** Option Accessory



Model Name  
**Switched PDU**



Model Number  
**ATP-3011M-24-N3**

30Amp 115V



General	
Output	(24) NEMA 5 -20/15R
Input	(1) NEMA L5 -30P attached power cord, 3 meters long
Protection	(3) 20 AMP Circuit Breaker
Communication	
DHCP Indication	(1) Green LED
Circuit Status	(3) Red LED
Output Status	(24) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segment for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- 2%+/- 0.1AMP
Operation	
Nominal Voltage	115V
Voltage	100V-127V full range
Frequency	50/60HZ full range
Max. Output Current	30 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1778 x 44 mm
Weight	6.4 kg
Regulatory Approvals	CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 FCC Part 15 Class A, ICES-003

**Meter** True RMS Current Meter

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual, Group, Schedule, Auto Ping

**Power Delay** Power On/Off Sequence can be Defined

**Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload

**Event Alert** Email, Trap, Audible Alarm

**Temp./Humidity** Option Accessory



Model Name  
**Switched PDU**



Model Number  
**ATP-3020P-16-N2**

30Amp 208V



**General**

Output	(8) NEMA 5 -15/20R
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to NEMA 5 -15P PowerCord 3 Meters long
Protection	(1) 15 AMP Circuit Breaker

**Communication**

DHCP Indication	(1) Green LED
Output Status	(8) Green LED
Circuit Status	(1) Red LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segments for PDU Identification
Meter	3 Digits Seven Segments

**Power Information**

Voltage	+/- 2% @ 90V~260V
Active Power	+/- 2% @ 50W~5000W
Apparent Power	+/- 2% @ 50VA~5000VA
Frequency	+/- 2% @ 45~65Hz
PowerFactor	+/- 0.02 @ 0.5~1.0
kWh	Range: 0.00kWh ~ 99999.999kWh Precision: +/- 2% @ 50W~5000W, kh=1.0
Current	Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- 2% +/- 0.1AMP

**Operation**

Nominal Input Voltage	115V
Output Voltage	100V- 127V full range
Frequency	50/60HZ full range
Max. Output Current	15 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	125 x 432 x 44.45 mm
Net Weight	2.5 kg

**Regulatory Approvals**



**Meter** True RMS Current Meter

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual, **Power Delay** Power On/Off Sequence can be Defined

**Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload

**Event Alert** Email, Trap, Audible Alarm

**Temp./Humidity** Option Accessory



Model Name  
**Switched PDU**



Model Number  
**ATP-3020P-24-N3**

30Amp 208V



General	
Output	(2) IEC320 C13 (3) IEC320 C19
Input	(1) NEMA6 -30P attached powercord, 3 meters long
Protection	(3) 16 AMP Circuit Breaker
Communication	
DHCP Indication	(1) Green LED
Circuit Status	(3) Red LED
Output Status	(24) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segment for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- -2%/+/- 0.1AMP
Operation	
Nominal Voltage	208V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	30 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1778 x 44 mm
Weight	6 kg
Regulatory Approvals	CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 C-Tick AS/NZS CISPR 22: 2006 FCC Part 15 Class A, ICES-003

**Meter** True RMS Current Meter

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual, **Power Delay** Power On/Off Sequence can be Defined

**Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload

**Event Alert** Email, Trap, Audible Alarm

**Temp./Humidity** Option Accessory



Model Name  
**Switched PDU**



Model Number  
**ATP-3223C-24-N3**

32Amp 230V



**General**

Output	(21) IEC320 C13 (3) IEC320 C19
Input	(1) IEC320 309 attached powercord, 3 meters long
Protection	(3) 16 AMP Circuit Breaker

**Communication**

DHCP Indication	(1) Green LED
Circuit Status	(3) Red LED
Output Status	(24) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segment for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- 2%+/- 0.1AMP

**Operation**

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	32 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1778 x 44 mm
Weight	6 kg

**Regulatory Approvals**  
 CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3  
 C-Tick AS/NZS CISPR 22: 2006  
 FCC Part 15 Class A, ICES-003



- Meter** True RMS Current Meter,
- Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
- Protocols** TCP/IP, SNMP, DHCP, UDP
- Outlet Control** Individual,
- Power Delay** Power On/Off Sequence can be Defined
- Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload
- Event Alert** Email, Trap, Audible Alarm



Model Name  
**Switched PDU**



Model Number  
**ATP-1623K-08-N1**

16Amp 230V



**General**

Output	(8) IEC320 C13
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 Power Cord 3 Meters long
Protection	(1) 16 AMP Circuit Breaker

**Communication**

DHCP Indication	(1) Green LED
Output Status	(8) Green LED
Circuit Status	(1) Red LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segments for PDU Identification
Meter	3 Digits Seven Segments

**Power Information**

Voltage	+/- 2% @ 90V-260V
Active Power	+/- 2% @ 50W-5000W
Apparent Power	+/- 2% @ 50VA-5000VA
Frequency	+/- 2% @ 45-65Hz
Power Factor	+/- 0.02 @ 0.5-1.0
kWh	Range: 0.001kWh ~ 99999.999kWh Precision: +/- 2% @ 50W-5000W, kh=1.0
Current	Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- 2% +/- 0.1AMP

**Operation**

Nominal Input Voltage	230V
Output Voltage	200V- 240V full range
Frequency	50/60HZ full range
Max. Output	16 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	125 x 432 x 44.45 mm
Net Weight	2.5 kg

**Meter** True RMS Current Meter, Voltage, Frequency, Power Factor, Active Power, Apparent Power, Total kWh, Sub-total kWh.

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual, Group, Schedule, Auto Ping

**Power Delay** Power On/Off Sequence can be Defined

**Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload

**Event Alert** Email, Trap, Audible Alarm

**Temp./Humidity** Option Accessory



Regulatory Approvals



Model Name  
**Switched PDU**



Model Number  
**ATP-3223C-16-N2**

32Amp 230V



**General**

Output	(14) IEC320 C13 (2) IEC320 C19
Input	(1) IEC320 309 attached powercord, 3 meters long
Protection	(2) 16 AMP Circuit Breaker

**Communication**

DHCP Indication	(1) Green LED
Circuit Status	(2) Red LED
Output Status	(16) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segment for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%+/-0.1AMP

**Operation**

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	32 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1245 x 44 mm
Weight	4.2 kg
Regulatory Approvals	CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 C-Tick AS/NZS CISPR 22: 2006 FCC Part 15 Class A, ICES-003



- Meter** True RMS Current Meter,
- Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
- Protocols** TCP/IP, SNMP, DHCP, UDP
- Outlet Control** Individual, **Power Delay** Power On/Off Sequence can be Defined
- Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload
- Event Alert** Email, Trap, Audible Alarm





Model Name  
**Switched PDU**



Model Number  
**ATP-1623K-24-N1**

16Amp 230V



General	
Output	(21) IEC320 C13 (3) C19
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 PowerCord 3 Meters long
Protection	(1) 16 AMP Circuit Breaker
Communication	
DHCP Indication	(1) Green LED
Output Status	(24) Green LED
Network	(1) RJ45 for Ethernet
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- 2% +/- 0.1AMP
Operation	
Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1245 x 44 mm
Weight	4.6 kg
Regulatory Approvals	CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 C-Tick AS/NZS CISPR 22: 2006



- Meter** True RMS Current Meter,
- Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
- Protocols** TCP/IP, SNMP, DHCP, UDP
- Outlet Control** Individual,
- Power Delay** Power On/Off Sequence can be Defined
- Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload
- Event Alert** Email, Trap, Audible Alarm



Model Name  
**Switched PDU**



Model Number  
**ATP-1623K-16-N2**

2x16Amp 230V



**General**

Output	(8) IEC320 C13 (8) IEC320 C19
Input	(2) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 Power Cord 3 Meters long
Protection	(2) 16 AMP Circuit Breaker

**Communication**

DHCP Indication	(1) Green LED
Circuit Status	(2) Red LED
Output Status	(16) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segment for PDU Circuit Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/ -2%/ -0.1AMP

**Operation**

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp for Each Branch
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	215 x 432 x 44 mm
Weight	4.4 kg

Regulatory Approvals



**Meter** True RMS Current Meter

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual, Group, Schedule, Auto Ping

**Power Delay** Power On/Off Sequence can be Defined

**Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload

**Event Alert** Email, Trap, Audible Alarm

**Temp./Humidity** Option Accessory



Model Name  
**Switched PDU**



Model Number  
**ATP-1623K-16-N1**

16Amp 230V



**General**

Output	(14) IEC320 C13 (2) C19
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 Power Cord 3 Meters long
Protection	(1) 16 AMP Circuit Breaker

**Communication**

DHCP Indication	(1) Green LED
Output Status	(16) Green LED
Network	(1) RJ45 for Ethernet
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- 2% +/- 0.1AMP

**Operation**

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp (UL derated 12 Amp)
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1245 x 44 mm
Weight	3.7 kg
Regulatory Approvals	UL 60950 -1, UL Listed, CSA, cULListed, CB by UL CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 C-Tick AS/NZS CISPR 22: 2006



**Meter** True RMS Current Meter

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual, Group, Schedule, Auto Ping

**Power Delay** Power On/Off Sequence can be Defined

**Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload

**Event Alert** Email, Trap, Audible Alarm



Model Name  
**Switched PDU**



Model Number  
**ATP-1623K-08-N1**

16Amp 230V



**General**

Output	(8) IEC320 C13
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 PowerCord 3 Meters long
Protection	(1) 16 AMP Circuit Breaker

**Communication**

DHCP Indication	(1) Green LED
Output Status	(8) Green LED
Network	(1) RJ45 for Ethernet
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- 2% +/- 0.1AMP

**Operation**

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp (UL derated 12 Amp)
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	90 x 432 x 44 mm
Weight	2.1 kg
Regulatory Approvals	UL 60950 -1, UL Listed, CSA, cUL Listed, CB by UL CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 C-Tick AS/NZS CISPR 22: 2006



**Meter** True RMS Current Meter,

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual, **Power Delay** Power On/Off Sequence can be Defined

**Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload

**Event Alert** Email, Trap, Audible Alarm



Model Name  
**Switched PDU**



Model Number  
**ATP-1623K-02-N1**

16Amp 230V



**General**

Output	(2) IEC320 C13
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 PowerCord 3 Meters long
Protection	(1) 16 AMP Circuit Breaker

**Communication**

DHCP Indication	(1) Green LED
Output Status	(2) Green LED
Network	(1) RJ45 for Ethernet
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- 2%+/- 0.1AMP

**Operation**

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp (UL derated 12 Amp)
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	90 x 254 x 44 mm
Weight	1 kg
Regulatory Approvals	CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 C-Tick AS/NZS CISPR 22: 2006



**Meter** True RMS Current Meter,

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual,

**Power Delay** Power On/Off Sequence can be Defined

**Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload

**Event Alert** Email, Trap, Audible Alarm



Model Name  
**Switched PDU**



Model Number  
**ATP-1023J-08-N1**

10Amp 230V



**General**

Output	(8) IEC320 C13
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to C14 PowerCord 3 Meters long
Protection	(1) 10 AMP Circuit Breaker

**Communication**

DHCP Indication	(1) Green LED
Output Status	(8) Green LED
Network	(1) RJ45 for Ethernet
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- 2% +/- 0.1AMP

**Operation**

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	10 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	90 x 432 x 44 mm
Weight	2 kg
Regulatory Approvals	UL 60950 -1, UL Listed, CSA, cUL Listed, CB by UL CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 C-Tick AS/NZS CISPR 22: 2006



**Meter** True RMS Current Meter,

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual, **Power Delay** Power On/Off Sequence can be Defined

**Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload

**Event Alert** Email, Trap, Audible Alarm



Model Name  
**Switched PDU**



Model Number  
**ATP-1023J-02-N1**

10Amp 230V



**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual, Group, Schedule, Auto Ping

**Event Alert** Email, Trap

Specification

**General**

Output	(2) IEC320 C13
Input	(1) IEC320 C14 Inlet; Enclosed IEC320 C13 to C14 Power Cord 1.8 Meters long
Reset	Press reset hole by clip and wait 6 flashes of "Signal" LED; then NPS can reset back to default setting.

**Communication**

Reset Indication	(1) Yellow LED
Power Status	(1) Red LED
Output Status	(1) Green LED
Network	(1) RJ45 for Ethernet

**Operation**

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	10 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	120 x 100 x 40 mm
Weight	0.8 kg
Regulatory Approvals	CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 FCC Part 15 Class A, PSE



Model Name  
**Switched PDU**



Model Number  
**ATP-1023J-01-N1**

10Amp 230V



**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual, Group, Schedule, Auto Ping

**Event Alert** Email, Trap

Specification

**General**

Output	(1) IEC320 C13
Input	(1) IEC320 C14 Inlet; Enclosed IEC320 C13 to C14 Power Cord 1.8 Meters long
Reset	Press reset hole by clip and wait 6 flashes of "Signal" LED; then NPS can reset back to default setting.

**Communication**

Reset Indication	(1) Yellow LED
Power Status	(1) Red LED
Output Status	(1) Green LED
Network	(1) RJ45 for Ethernet

**Operation**

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	10 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	120 x 100 x 40 mm
Weight	0.8 kg
Regulatory Approvals	CE, EN 55032 Class A, EN 55024, EN 61000 -3-2, EN 61000-3-3 FCC Part 15 Class A, PSE





Model Name

# Switched PDU (3 Phase)

Model Number

## ATP-3240C-24-N6



22kW 32Amp 3 Phase



General	
Output	(18) IEC320 C13 (6) IEC320 C19
Input	(1) IEC320 309 attached powercord, 3 meters long
Protection	(6) 16 AMP branch type breaker
Communication	
DHCP Indication	(1) Green LED
Circuit Status	(6) Red LED
Output Status	(24) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segments for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- 2%+/- 0.1AMP
Operation	
Nominal Voltage	400V AC, 3 -Phase 3P+N+PE
Voltage	230V
Frequency	50/60HZ full range
Load Capacity	22 kVA
Max. Input	32 Amp
Max. Output Current (Outlet)	IEC 320 C13: 10A IEC 320 C19: 16A
Max. Output Current (Bank)	16 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1645 x 80 mm
Weight	8.2 kg
Regulatory Approvals	CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3



**Meter** True RMS Current Meter,

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual,

**Power Delay** Power On/Off Sequence can be Defined

**Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload

**Event Alert** Email, Trap, Audible Alarm

**Temp./Humidity** Option Accessory



Model Name

# Switched PDU (3 Phase)

Model Number

# ATP-1640C-24-N3



11kW 16Amp 3 Phase



### General

Output	(2) IEC320 C13 (3) IEC320 C19
Input	(1) IEC320 309 attached power cord, 3 meters long
Protection	(3) 16 AMP breaker

### Communication

DHCP Indication	(1) Green LED
Circuit Status	(3) Red LED
Output Status	(24) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segments for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/- 2%+/- 0.1AMP

### Operation

Nominal Voltage	400V AC, 3 -Phase 3P+N+PE
Voltage	230V
Frequency	50/60HZ full range
Load Capacity	11.1 kVA
Max. Input	16 Amp
Max. Output Current (Outlet)	IEC 320 C13: 10A IEC 320 C19: 16A
Max. Output Current (Bank)	16 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1645 x 80 mm
Weight	5.7 kg
Regulatory Approvals	CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3



**Meter** True RMS Current Meter,

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** TCP/IP, SNMP, DHCP, UDP

**Outlet Control** Individual, **Power Delay** Power On/Off Sequence can be Defined

**Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload

**Event Alert** Email, Trap, Audible Alarm

**Temp./Humidity** Option Accessory

