

Model Name
Switched PDU



Model Number
ATP-3223C-24-N3

32Amp 230V



General

Output	(21) IEC320 C13 (3) IEC320 C19
Input	(1) IEC320 309 attached powercord, 3 meters long
Protection	(3) 16 AMP Circuit Breaker

Communication

DHCP Indication	(1) Green LED
Circuit Status	(3) Red LED
Output Status	(24) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
PDU ID	1 Digits Seven Segment for PDU Identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/ -2%+/-0.1AMP

Operation

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	32 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	56 x 1778 x 44 mm
Weight	6 kg
Regulatory Approvals	CE



Meter True RMS Current Meter,

Power Monitor Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

Protocols TCP/IP, SNMP, DHCP, UDP

Outlet Control Individual,

Power Delay Power On/Off Sequence can be Defined

Alarm Thresholds User-Defined Alarm Thresholds for Warning and Overload

Event Alert Email, Trap, Audible Alarm

